

## SUPPORT

compatible fluoros, controllable by the LFXHub

Please find the current list on [www.movie-inter.com](http://www.movie-inter.com)  
or send an [eMail](mailto:info@movie-inter.com) .



phone +49 (0)30-2232 0575  
fax +49 (0)30-2232 0571  
web [www.movie-inter.com](http://www.movie-inter.com)  
mail [info@movie-inter.com](mailto:info@movie-inter.com)

page 1 of 2

compatible fluoros, 5-100% dimmable with the LFXHub:

fixture	manufacturer	DMX IN	analog input	preferred control with LFXHub / hints
DivaLite 200/400	KinoFlo	-	yes	control via REMOTE DIM only > KinoFlo control cable (order code: kflo)
Parabeam 200/400		yes	yes*	DMX, analog control using the REMOTE DIM input will result in an *undesirable "smooth" effect.
ParaZip 200/400		yes	yes*	
T5 classic	Softlights	yes	-	DMX, at fixture turn dimmer level to zero for control with the LFXHub!
T5 BIG ONE		yes	-	
T5 small		yes	-	
T5 medium		yes	-	
T5 long one		yes	-	
Highlight 110	Photon Beard	yes	-	must have DMX option installed, at fixture turn dimmer level to zero for control with the LFXHub!
Highlight 220		yes	-	
Highlight 330		yes	-	
Highlight 440		yes	-	
Radiant 170		yes	-	
Studio 255 DMX	Cotelux	yes	-	must have DMX option installed
Studio 455 DMX		yes	-	
Studio 655 DMX		yes	-	
Studio 855 DMX		yes	-	
Starlight 1000 DMX	Lupo	yes	yes**	must have DMX option installed, ** 0-10 VDC control requires optional control cable
Quadrilight 2000 DMX		yes	yes**	
Superlight 2000 DMX		yes	yes**	
Striplight 1000 DMX		yes	yes**	
FB 4/2 P	PowerGems	yes	-	
NesyLite 110	Nesys	yes	-	must have DMX option installed
NesyLite 220		yes	-	
NesyLite 330		yes	-	
NesyFlex 110		yes	-	
NesyFlex 220		yes	-	
NesyFlex 220		yes	-	
NesyFlex 330		yes	-	
NesyFlex 440		yes	-	
NesyFlex 660		yes	-	
Lumpanels	Lumapanel	yes	-	DMX controlled with multiple channels

## SUPPORT

compatible fluoros, controllable by the LFXHub

Please find the current list on [www.movie-inter.com](http://www.movie-inter.com)  
or send an [eMail](mailto:info@movie-inter.com) .



phone +49 (0)30-2232 0575  
fax +49 (0)30-2232 0571  
web [www.movie-inter.com](http://www.movie-inter.com)  
mail [info@movie-inter.com](mailto:info@movie-inter.com)

page 2 of 2

The table shown below contains lamps using the "switched DMX mode". It means a tube is switched on at a certain dim level. Turn switch of lamp to "fixture" mode for DMX control.  
E.g. with a 4 Bank ballast tube #1 is on from 12 % dim level, tube #1 and #2 are on from 37% dim level, lamp #1-3: 64 %, all lamps from 84% dim level. For detailed information how to set up the DMX addresses please refer to the corresponding user manual.

compatible fluoros, **switchable** with the LFXHub via DMX:

fixture	manufacturer	mode	perfect for effects of the LFXHub
4 Bank DMX Ballast	KinoFlo	switched DMX	flasher, sequenzer, neon sign FX, ...
VistaBeam 300/600			
Image 85/45			

This compatability list is updated as soon we have further information about compatibel units. Please find the current list on <http://www.movie-inter.com> > Support > Downloads  
Do you know another compatible fluoro? Other users will be thankfull for any hint.  
Please send us a short [eMail](mailto:info@movie-inter.com) . Thank you.

manufacturer	web
KinoFlo	<a href="http://www.kinoflo.com">http://www.kinoflo.com</a>
Softlights	<a href="http://www.softlights.com">http://www.softlights.com</a>
Photon Beard	<a href="http://www.photonbeard.com">http://www.photonbeard.com</a>
Lumapanel	<a href="http://www.lumapanel.com">http://www.lumapanel.com</a>
Cotelux	<a href="http://www.cotelux.com">http://www.cotelux.com</a>
Lupo	<a href="http://www.lupo.it">http://www.lupo.it</a>
Nesys	<a href="http://www.nesys.de">http://www.nesys.de</a>